


Halide light source

5905339107305



Kanlux JC is a halogen light source with G4 and GY6.35 light bulb base.

GENERAL DATA:

Width [mm]: 10
Height [mm]: 40
Diameter [mm]: 10
Depth [mm]: 10
Mercury content: no

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC
Rated power [W]: 20
Lampshade material: glass
Total rated luminous flux [lm]: 330
Useful luminous flux of the light source Φ_{use} [lm]: 330
Useful luminous flux of the light source Φ_{use} [lm]: in sphere (360°)
Colour temperature: Warm white
Correlated colour temperature [K]: 2700
Colour rendering index: 100
Cap: GY6,35
Rated lamp-service life [h]: 2000
Number of on/off cycles: ≥ 8000
Annual power consumption [kWh/1000h]: 21
Luminous efficiency of the lamp [lm/W]: 17
Ignition time [s]: $\leq 0,1$
Lamp-heating time to 60% of the full luminous flux [s]: < 1

LOGISTIC DATA:

Packaging method: 50
Number of units in the secondary packaging: 50
Number of units in the packaging: 1000
Net unit weight [g]: 2
Grammage [g]: 6.35
Length of a unit pack [cm]: 2
Width of a unit pack [cm]: 2
Height of a unit pack [cm]: 5
Weight of a cardboard box [kg]: 6.35
Width of a cardboard box [cm]: 23.5
Height of a cardboard box [cm]: 24.5
Length of a cardboard box [cm]: 57
Volume of a cardboard box [m³]: 0.032818

Halide light source

