


## 24521 ZUBI LED 3,5W G9-CW

LED light source

5905339245212



Kanlux ZUBI LED are energy-saving sources. Their additional functional benefits include the small size and the milky lampshade reducing the glare effect. They provide smart and aesthetic look. The construction of Kanlux ZUBI sources guarantees a wide light emission angle, owing to which they are perfect for all open luminaires and chandeliers.

### TYPE OF LIGHT SOURCE:

**Lighting technology used:** LED

**Non-directional or directional light source:** NDLS

**Mains or non-mains light source:** MLS

**Connected light source (CLS):** no

**Colour-tuneable light source:** no

**High luminance light source:** no

**Anti-glare shield:** no

**Dimmable:** no

### PRODUCT PARAMETERS:

**Colour:** white

**Compatible with a dimmer:** no

**Width [mm]:** 16.5

**Height [mm]:** 48.5

**Depth [mm]:** 16.5

**Diameter [mm]:** 16.5

**Mercury content:** no

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Lamp rated current [mA]:** 32

**Rated power [W]:** 3.5

**Total rated luminous flux [lm]:** 300

**Rated beam angle [°]:** 320

**Material:** plastic

**Light source:** G9

**Diode type:** LED SMD

**Colour temperature:** cold white

**Cap:** G9



**Rated lamp-service life [h]:** 15000

**Number of on/off cycles:** ≥10000

**Light source shape:** kapsulka

## 24521 ZUBI LED 3,5W G9-CW

LED light source



### PARAMETERS FOR LED AND OLED LIGHT SOURCES:

**Energy consumption in on-mode of the light source (kWh/1000h):** 4  
**Energy efficiency class:** F  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** 300  
**Useful luminous flux of the light source  $\Phi_{use}$  [lm]:** in sphere (360°)  
**Correlated colour temperature [K]:** 6000  
**Colour consistency in McAdam ellipses:**  $\leq 6$   
**On-mode power of the light source  $P_{on}$  [W]:** 3.5  
**Height of the light source [mm]:** 48.5  
**Width of the light source [mm]:** 16.5  
**Depth of the light source [mm]:** 16.5  
**Colour rendering index:** 80  
**Chromaticity coordinates (x):** 0.318  
**Chromaticity coordinates (y):** 0.34  
**Claim of equivalent power [W]:** 28  
**R9 colour rendering index value:** 19  
**Survival factor:**  $\geq 0.9$   
**The lumen maintenance factor:** 0.93

### PARAMETERS FOR LED AND OLED MAINS LIGHT SOURCES:


**Displacement factor ( $\cos \phi_1$ ):** 0.4  
**LED light source replaces a fluorescent light source without integrated ballast of a particular wattage:** Not applicable  
**Flicker metric (Pst LM):**  $\leq 1,0$   
**Stroboscopic effect metric (SVM):**  $\leq 0,4$

### LOGISTIC DATA:

**Packaging method:** 10  
**Number of units in the secondary packaging:** 10  
**Number of units in the packaging:** 100  
**Net unit weight [g]:** 12  
**Grammage [g]:** 46.8  
**Length of a unit pack [cm]:** 11.5  
**Width of a unit pack [cm]:** 3  
**Height of a unit pack [cm]:** 16.5  
**Weight of a cardboard box [kg]:** 4.68  
**Width of a cardboard box [cm]:** 41  
**Height of a cardboard box [cm]:** 17.5  
**Length of a cardboard box [cm]:** 64  
**Volume of a cardboard box [m<sup>3</sup>]:** 0.04592

## 24521 ZUBI LED 3,5W G9-CW

LED light source



KANLUX S.A. (kat 24521) ZUBI LED 3,5W G9-CW / LDC (Polar)

Luminaire: KANLUX S.A. (kat 24521) ZUBI LED 3,5W G9-CW  
Lamps: 1 x ZUBI LED 3,5W G9-CW

