

08951 LED12 SMD G4-WW


LED light source


5905339089519













Kanlux LED12 is a capsule with G4 screw based on SMD LEDs. The source's illumination angle is 160 $^{\circ}$, and its durability amounts to 20,000 hours.

GENERAL DATA:

Colour: white

Lamp designed for decorative lighting: no

Compatible with a dimmer: no

Height [mm]: 41 Diameter [mm]: 30 Mercury content: no

TECHNICAL DATA:

Rated voltage [V]: 12 DC Rated power [W]: 1.5

Light source: JC **Diode type**: LED SMD

Total rated luminous flux [lm]: 130 Colour temperature: Warm white Colour temperature [K]: 3000 Colour uniformity [SDCM]: ≤6 Colour-rendering index Ra: ≥80

Cap: G4

Rated lamp-service life [h]: 20000 Number of on/off cycles: ≥10000

Rated beam angle [°]: 160 Light source EEI: A++

Lamp rated current [mA]: 160

Annual power consumption [kWh/1000h]: 2 Luminous efficiency of the lamp [lm/W]: 87

Ignition time [s]: ≤ 0.5

Lamp-heating time to 60% of the full luminous flux [s]:

Negligible

Lamp-heating time to 95% [s]: <2

Lamp premature-failure indicator: <5% po 1000h

Lamp service life factor after the period of 6000h [%]:

≥90

Luminous flux retention factor at the end of rated

service life [%]: ≥70

Luminous flux retention factor after the period of 6000h

[%]: ≥80

Declaration of equality in power rating [W]: 14

Rated peak light intensity [cd]: 45


LOGISTIC DATA:





08951 LED12 SMD G4-WW

LED light source



Unit of measurement: unit **Packaging method**: 20

Number of units in the secondary packaging: 20


Number of units in the packaging: 200

Net unit weight [g]: 4 Grammage [g]: 11.5

Length of a unit pack [cm]: 3.5
Width of a unit pack [cm]: 2
Height of a unit pack [cm]: 4.5
Weight of a cardboard box [kg]: 2.3
Width of a cardboard box [cm]: 25
Height of a cardboard box [cm]: 20
Length of a cardboard box [cm]: 36
Volume of a cardboard box [m³]: 0.018

ADDITIONAL INFORMATION:

 LED electric power supply is needed for proper functioning, e.g. POWELED, DRIFT or TRETO available in the Kanlux product range



KANLUX S.A. (kat 8951) LED12 SMD G4-WW / LDC (Polar)

