



TECHNICAL INFORMATION

Watts:	48
Lumens:	3840
Input Power:	AC:200-240V, 50/60Hz
Long Life:	20,000 Hours
Unit Color:	White
Body Type:	PC
PF:	>0.9
LED Chip Type:	SMD
CRI:	>70
Operation Temperature:	-20°C to +40°C
Dimmable:	No
Beam Angle:	120°
Color:	4000K
Dimension:	1500x65x58mm
Linkable:	Upto 6 Units

G SERIES

V-TAC's LED Lighting range includes lighting that fulfills the needs of various end-users and industries, offering efficient and innovative products that provide modern solutions at an affordable price. We are proud to also provide extended multi-year warranty on our products, as well as detailed support.

One brand, endless solutions..

SKU: 6287 - 1415 940

[View more details](#)



IP65
RATING



2 YEAR
WARRANTY



IK 06



SAVE UP TO
80%
ENERGY

FEATURES

- Using high power SMD technology which makes it more reliable and durable
- Complete protection from water, dust and corrosion - IP65 Rated
- Designed for maximum efficiency & minimal glare
- Excellent heat dissipation
- Suitable for parking lots, warehouses, garages, storage docks, workshops etc.

CE/EMC

CE/LVD



PACKAGING

Gross Weight (Kgs):	1.2
Unit CBM:	0.007189
Dimension:	1500x65x58mm

MASTER BOX PACKAGING

Box Qty:	12
Qty Per Pallet:	144
Length (Box) mm:	1570
Width (Box) mm:	70
Height (Box) mm:	60

LISTING DETAILS

Commodity Code:	9405403990
EanCode:	3800157616515