


## 23240 KMC-20-20

Modular contactor, 230 VAC control voltage

5905339232403



Contactors are used for automatic activation of electricity receivers. Categories of use AC7a, AC7b.

### GENERAL DATA:

**Utilisation category:** AC-7A, AC-7B

**Colour:** white

**Place of assembly:** rail TH35

**Place of application:** Indoors

**Norm:** PN-EN 60947-4-1

### TECHNICAL DATA:

**Rated voltage [V]:** 230 AC

**Rated frequency [Hz]:** 50

**Ambient temperature range to which the product can be exposed:** -25÷40

**Connection type:** Terminal block

**Number of n.o./n.c. contacts:** 2/0

**Number of modules:** 1

**Rated power AC-7A/230:** 4kW

**Rated power AC-7B/230:** 1,2kW

**Coil-supply voltage [V]:** 230V AC 50/60Hz

**Rated current I(N) AC-7A/AC-1:** 20A

**Rated current I(N) AC-7B/AC-1:** 7A

**IP class:** 20

### LOGISTIC DATA:

**Packaging method:** 12

**Number of units in the secondary packaging:** 12

**Number of units in the packaging:** 120

**Net unit weight [g]:** 120

**Grammage [g]:** 130

**Length of a unit pack [cm]:** 2

**Width of a unit pack [cm]:** 7.5

**Height of a unit pack [cm]:** 8.5

**Weight of a cardboard box [kg]:** 15.6

**Width of a cardboard box [cm]:** 25

**Height of a cardboard box [cm]:** 19.5

**Length of a cardboard box [cm]:** 45

**Volume of a cardboard box [m<sup>3</sup>]:** 0.021938

## **23240** KMC-20-20

---

Modular contactor, 230 VAC control voltage